

ALCATEL MODEL: FC02000715 FOR ASM 180T, 180TD, 180TD+, 182T, 182TD, 182TD+

LEAK RATE: LOW 10⁻⁷ MBARL/SEC

LEAK ELEMENT: TEFLON PERMEATION (SLOW RESPONSE)

GAS: HELIUM (100%)

OF CAL PTS: 1

RESERVOIR STYLE: ALCATEL INTERNAL - 180T (ALUMINUM CONSTRUCTION)

EST. DEPL. RATE: 0.3%/YEAR

ISOLATION VALVE: NONE

OUTLET CONNECTION: NW16 FLANGE

OUTLET PRESSURE: VACUUM

REFILLABLE: NO

WARRANTY: NONE



NON-REFILLABLE

ALUMINUM RESERVOIR

NW16 FLANGE



REFILLABLE

SS RESERVOIR

LACO MODEL: CM3IL-71080V0/4 FOR ASM 180T, 180TD, 180TD+, 182T, 182TD, 182TD+

LEAK RATE: LOW 10⁻⁷ MBARL/SEC

LEAK ELEMENT: UNBREAKABLE GLASS PERMEATION (QUICK RESPONSE)

GAS: HELIUM (100%)

OF CAL PTS: 1

RESERVOIR STYLE: ALCATEL INTERNAL - 180T (STAINLESS STEEL CONSTRUCTION)

EST. DEPL. RATE: 0.3%/YEAR

ISOLATION VALVE: NONE

OUTLET CONNECTION: NW16 FLANGE

OUTLET PRESSURE: VACUUM

REFILLABLE: YES

WARRANTY: LIFETIME

